

## GORE® DF Sealing tape



### Description

GORE® DF mono-axial expanded PTFE sealing tape, self-adhesive tape to facilitate assembly. Universally chemical resistant with the exception of molten alkali metals and elemental fluorine, pH 0-14.

### Technical properties

- chemical resistant
- great adaptability
- does not age
- easily mountable

### Applicable

For industrial use only. Not suitable for usage in the manufacturing, processing or

packaging of food and pharma, cosmetics or medical products.

### Chemical resistance, pressure and temperature

Pressure max 10 bar

Temperature -240°C to max +270 °C

### Supplu programme

The tape is available in various sizes, see table 1

### Approvals and certificates

- BAM
- DVGW
- TA-Lüft

Table 1: Supply programme

Length	Coil	Thickness	Part no.
25	3	1,5	10001452
25	5	2	10001454
25	7	2,5	10001455
10	10	3	10001443
10	14	5	10001445
10	17	6	10001447
5	20	7	10001449

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or in-complete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

For more information, quotations or orders: Phone +31 (0)72 514 15 14 or E-mail [info@eriks.nl](mailto:info@eriks.nl)