

NBR White



Material
NBR

Color
white

Density (gr/cm³)
±1,39

Hardness (°Shore)
60 ±5

Pressure max. (bar)
10

Temperature range (°C)
-30°C tot max +80°C

Application
Food industry

Approvals and certificates

- EC1935
- FDA

Table 1: Technical data*

Properties	Test standard	Value	Unit
Max surface pressure σ_{v_0}	DIN 29090		MPa
Minimum temperature		-30	°C
Maximum temperature		+80	°C
Hardness	ISO 7619-1	60	Shore A
Elongation at break	DIN 53504	500	%
Tensile strength	DIN 53504	11	N/mm ²
Density		1,39	g/cm ³

* depending on temperature and construction

Table 2: Supply programme*

Thickness (mm)	Inserts	Width (mm)	Length (m)	Part no.
2	-	1400	10	12943773
3	-	1400	10	12699201
5	-	1400	10	12550808
10	-	1400	5	12586006

* Gaskets can be produced according to industry standards or according to drawings.

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

For more information, quotations or orders:

The Netherlands : +31 88 855 80 44 of gaskets@eriks.nl

Belgium : Dutch +32 3 210 91 10 of flangegaskets@eriks.be

Francophone +32 71 91 50 64 of flangegaskets@eriks.be

page 1/1